



TECHNICAL SPECIFICATION
FIBER DRUM (WITH MDF TOP-END)

Diameter	Volume
Ø360	25 Lt.
Ø360	50 Lt.
Ø400	60 Lt.
Ø400	80 Lt.
Ø450	100 Lt.
Ø517	165 Lt.
Ø585	240 Lt.
Ø600	230 Lt.
Ø600	280 Lt.
Ø650	250 Lt.
Ø650	330 Lt.

DIMENSIONS : See the technical drawing.

Material and Production Specifications:

Body is coiled up from kraft paper as lamination by glue between each layer. Reinforcement rings are fixed to the both ends of the body. Bottom-end is seamed to the body. Top-end is fixed to the body by a closing ring with lever mechanism.

- Body** : Kraftliner coiled up from kraft paper with glue in between.
- Rings** : Hot Dipped Galvanized Cold Rolled Steel, 0.60 mm.
- Bottom-End** : MDF. (Medium Density Fiberboard)
- Top-End** : MDF. (Medium Density Fiberboard).
- Closing Ring** : Manufactured of Hot Dipped Galvanized Steel, sealable closing ring with lever.
- Marking** : Production date is coded on the bottom-end. Any other coding can be made with silk-screening system on the body of the drum.
- Tests** : All in process and final product tests are undertaken according to ISO 9001:2015 Quality Management System and test results are informed to the customer by Quality Reports.



İZVAR AMBALAJ SANAYİ VE TİCARET A.Ş.
Merkez : Acarlar İş Merkezi F-Blok K3 No 10 Kavacık 34805, Beykoz İstanbul
Tel: ++ 90 216 6802080 Faks: ++ 90 216 6802090
Fabrika : Tavşantepe Sk. No 74 Pelitli 41490, Gebze Kocaeli
Tel: ++ 90 262 7510220 Faks: ++ 90 262 7510221



www.izvar.com